

KH Type

サイズ 100mm・130mm

重荷重用固定金具



RGKHK-100



RGKH-150



RKH-150

単位：mm

単位：mm												
サイズ 	品番	車輪仕様	軸受	最大荷重 		タイヤ幅 R 	シャフト径 D 	取付高さ H1 	トッププレート F1/F2 	取付穴ピッチ P1/P2 	取付穴径 d 	自重 (g) 
				(daN)	(kgf)							
100	RGNKH-100	強化ナイロン	B/B入	460	469.2	45	12	144	139/88	103/52	11	1,450
	RGKH-100	アルミ製ゴム	B/B入	200	204.0	50						1,480
	RKH-100	アルミ製ウレタン	B/B入	300	306.0							1,480
	RFKH-100	鋼板製ウレタン	B/B入									1,490
	RRKH-100	MCナイロン	B/B入	460	469.2							1,390
	UWBKH-100	MCナイロン	B/B入			29						1,330
130	RGKH-130	アルミ製ゴム	B/B入	240	244.8	50	20	177	140/96	100/56	11	2,400
	RKH-130	アルミ製ウレタン	B/B入	450	459.0							2,540
	RFKH-130	鋼板製ウレタン	B/B入									2,570
	RRKH-130	アルミ製MCナイロン	B/B入	500	510.0	36						2,550
	UWBKH-130	MCナイロン	B/B入									2,300

軸受 B/B入：鋼板製ベアリング入り

車輪 詳細はP.97以降をご参照下さい。

【金具寸法】

単位：mm

サイズ 	最大荷重 		金具高さ H 	フォーク幅 B 	金具板厚 t 	自重 (g)
	(daN)	(kgf)				
100	460	469.2	94	57	4.5	950
130	500	510.0	112	60	5.0	1,490
150	550	561.0	123	60	5.0	1,520
200	800	816.0	150	71	5.0	2,260

※金具にはシャフトセット(シャフト・バネ座金・ナット)が付属します。

KH Type

サイズ 150mm・200mm

重荷重用固定金具



RFBK-150



RRKH-150



UWBKH-150

重荷重用キャスター

サイズ 	品 番	車輪仕様	軸受	最大荷重 		タイヤ 幅 R 	シャフト 径 D 	取付 高さ H1 	トップ プレート F1/F2 	取付穴 ピッチ P1/P2 	取付穴 径 d 	自重 (g) 
				(daN)	(kgf)							
150	RGKH-150	アルミ製ゴム	B/B入	300	306.0	50	20	198	140/96	100/56	11	2,650
	RKH-150	アルミ製ウレタン	B/B入	500	510.0							2,760
	RFBK-150	鋼板製ウレタン	B/B入	500	510.0							2,820
	RRKH-150	アルミ製MCナイロン	B/B入	550	561.0	40						2,760
	UWBKH-150	MCナイロン	B/B入	550	561.0							2,620
200	RGKH-200	鋼板製ゴム	B/B入	410	418.2	63	25	250	151/102	112/63	14	4,820
	RFBK-200	鋼板製ウレタン	B/B入	600	612.0							4,830
	RRKH-200	アルミ製MCナイロン	B/B入	660	673.2							4,670
	UWBKH-200	MCナイロン	B/B入	800	816.0	42						4,200

単位：mm

軸受 B/B入：鋼板製ベアリング入り

車輪 詳細はP.97以降をご参照下さい。

